

Signal and power backup avoid any image loss during living playing, Adjustable inclination angle is suitable for the best possible viewing and camera shooting angles. used in perimeter fence advertising and information transmission.



### Feature:



### Certificates:



### Feature:

#### Redundancy:

Signal and power backup avoid any image loss during living playing;

#### High refresh rate:

Outstanding refresh rate performance even at extremely low brightness situation;

#### Protection:

Rubber louvers and rubber padding guarantees safety of players and audiences;

#### Rotate leg design:


Rotate leg design could join the cabinet in the same level or combine together;

#### Easy installation:

With sided locks and precisely connectors, easy to install 2 cabinets together in a same level;

#### High contrast ratio:

More than 960Hz refresh rate and 5000:1 contrast ratio ensure the image color more vivid with broadcasting retransmit.



## PRODUCT SPECIFICATION

Item	Sport		
Model	SID-6S	SID-8S	SID-10S
Pixel Pitch (mm)	6	8	10
Pixel Density (dot/m <sup>2</sup> )	27,777	15,625	10,000
LED Type	SMD3528	SMD3528	SMD3528
Module Size (W x H x D)mm	192 x 192 x 15	256 x 128 x 15	320 x160 x 21
Module Resolution (W x H)	32 x 32	32 x 16	32 x 16
Module Weight (Kg)	0.32	0.28	0.45
Power Consumption per Module (W)	15	13	18
Driver Mode (Scan)	1/8	1/8	1/4
Brightness (cd/m <sup>2</sup> )	≥1,800	≥1,800	≥1,800
Grey Scale (bits)	14	14	14
Refresh Rate (Hz)	≥960	≥960	≥960
Cabinet Size (W x H x D)mm	1,152 x 960 x 160	1,024 x 896 x 160	960 x 800 x 165
Cabinet Resolution (W x H)	192 x 160	128 x 112	96 x 80
Cabinet Weight (Kg/m <sup>2</sup> )	50	50	50
Max Power Consumption (W/m <sup>2</sup> )	≤430	≤480	≤420
Average Power consumption (W/m <sup>2</sup> )	195	216	189
Viewing Angle	Degree: H	140°	
	Degree: V	140°	
Mini View Distance (m)	6	8	10
Use Temperature(°C)	Operating	-10°C~40°C/14°F~104°F	
	Storage	-20°C~50°C/-4°F~122 °F	
Input Voltage	100~240V		
Input Power Frequency (Hz)	50Hz-60Hz		
Failure Rate	<1/100,000		
Signal Input Format	SDI, RGBHV, YUV,YC, Composite, HDMI,DVI, SD/HD-SDI etc.		
Life Time (hrs)	100,000		
IP Level (Front / Rear)	IP43 / IP30		

Remark: Specifications are subject to change without notice.



BL.#7, Huamei Rd.#8, Songgang Av., Songgang Town, Bao'an District, Shenzhen, China.



Tel: 86-755-2359 0202



Fax: 86-755-2908 0303



E-mail: info@q-color.com



Web: www.q-color.com



International hotline:

**86-755-2359 0202**