

Indoor media advertising, Indoor live event / show broadcast

Slim and seamless surface. A clear and vivid color display. It's revolutionary design makes it the ideal solution for large events, exhibitions, broadcasting and concert tours.



Slim Alloy – SA Series

Feature:



Certificates:



Feature:

Wide view angle:

With 140/140 degree view angle , bring a wonderful image;

Standard cabinet design:

Standardized cabinet structure design offers convenience for loading, shipping, installation, dismantle;

Fanless design:

Professional fanless design to make sure the noise less than 25db;

High refresh rate:

960Hz refresh rate and 5000:1 contrast ratio ensure the image color more vivid;

Slim cabinet design:

Slim and seamless surface with aluminum structure;

Different colors for optional:

Provide different cabinet colors to match customers' requirement.



PRODUCT SPECIFICATION

Item	Rental & Events				
	SA-3S	SA-4S	SA-5S	SA-6S	SA-7.62S
Model	SA-3S	SA-4S	SA-5S	SA-6S	SA-7.62S
Pixel Pitch (mm)	3	4	5	6	7.62
Pixel Density (dot/m ²)	111,111	62,500	40,000	27,777	17,222
LED Type	SMD2121	SMD2121	SMD3528	SMD3528	SMD3528
Module Size (W x H)mm	240 x 240 x 15	240 x 240 x 15	240 x 240 x 15	240 x 240 x 15	244 x 122 x 15
Module Resolution (W x H)	80 x 80	60 x 60	48 x 48	40 x 40	32 x 16
Module Weight (Kg)	0.52	0.52	0.51	0.5	0.28
Power Consumption per Module (W)	25	36	25	19	13
Driver Mode (Scan)	1/16	1/15	1/12	1/10	1/8
Brightness (cd/m ²)	≥1,200	≥1,200	≥1,800	≥1,800	≥1,800
Grey Scale (bits)	14	14	14	14	14
Refresh Rate (Hz)	≥960	≥960	≥960	≥960	≥960
Cabinet Size (W x H x D)mm	480 x 480 x 85	480 x 480 x 85	480 x 480 x 85	480 x 480 x 85	732 x 732 x 85
Cabinet Resolution (W x H)	160 x 160	120 x 120	96 x 96	80 x 80	96 x 96
Cabinet Weight (Kg/m ²)	45	45	45	45	45
Max Power Consumption (W/m ²)	≤450	≤750	≤550	≤430	≤550
Average Power consumption (W/m ²)	202	338	250	195	248
Viewing Angle	Degree: H				140°
	Degree: V				140°
Mini View Distance (m)	3	4	5	6	7.5
Use Temperature(°C)	Operating	-10°C~40°C/14°F~104°F			
	Storage	-20°C~50°C/-4°F~122 °F			
Input Voltage	100~240V				
Input Power Frequency (Hz)	50Hz-60Hz				
Failure Rate	<1/100,000				
Signal Input Format	SDI, RGBHV, YUV,YC, Composite, HDMI,DVI, SD/HD-SDI etc.				
Life Time (hrs)	100,000				
IP Level (Front / Rera)	IP 43 / IP30				

Remark: Specifications are subject to change without notice.



BL.#7, Huamei Rd.#8, Songgang Av., Songgang Town, Bao'an District, Shenzhen, China.



Tel: 86-755-2359 0202



Fax: 86-755-2908 0303



E-mail: info@q-color.com



Web: www.q-color.com



International hotline:

86-755-2359 0202