

Indoor media advertising, Indoor live event / show broadcast

Slim and seamless surface. A clear and vivid color display. It's revolutionary design makes it the ideal solution for large events, exhibitions, broadcasting and concert tours.



Slim Alloy – SA Series

Feature:



Certificates:



Feature:

Wide view angle:

With 140/140 degree view angle , bring a wonderful image;

Standard cabinet design:

Standardized cabinet structure design offers convenience for loading, shipping, installation, dismantle;

Fanless design:

Professional fanless design to make sure the noise less than 25db;

High refresh rate:

960Hz refresh rate and 5000:1 contrast ratio ensure the image color more vivid;

Slim cabinet design:

Slim and seamless surface with aluminum structure;

Different colors for optional:

Provide different cabinet colors to match customers' requirement.



BL.#7, Huamei Rd.#8, Songgang Av., Songgang Town, Bao'an District, Shenzhen, China.



Tel: 86-755-2359 0202



Fax: 86-755-2908 0303



E-mail: info@q-color.com



Web: www.q-color.com



International hotline:

86-755-2359 0202

PRODUCT SPECIFICATION

| Item | Rental & Events | | | | |
|---|---|------------------------|----------------|----------------|----------------|
| | SA-3S | SA-4S | SA-5S | SA-6S | SA-7.62S |
| Model | SA-3S | SA-4S | SA-5S | SA-6S | SA-7.62S |
| Pixel Pitch (mm) | 3 | 4 | 5 | 6 | 7.62 |
| Pixel Density (dot/m ²) | 111,111 | 62,500 | 40,000 | 27,777 | 17,222 |
| LED Type | SMD2121 | SMD2121 | SMD3528 | SMD3528 | SMD3528 |
| Module Size (W x H)mm | 240 x 240 x 15 | 240 x 240 x 15 | 240 x 240 x 15 | 240 x 240 x 15 | 244 x 122 x 15 |
| Module Resolution (W x H) | 80 x 80 | 60 x 60 | 48 x 48 | 40 x 40 | 32 x 16 |
| Module Weight (Kg) | 0.52 | 0.52 | 0.51 | 0.5 | 0.28 |
| Power Consumption per Module (W) | 25 | 36 | 25 | 19 | 13 |
| Driver Mode (Scan) | 1/16 | 1/15 | 1/12 | 1/10 | 1/8 |
| Brightness (cd/m ²) | ≥1,200 | ≥1,200 | ≥1,800 | ≥1,800 | ≥1,800 |
| Grey Scale (bits) | 14 | 14 | 14 | 14 | 14 |
| Refresh Rate (Hz) | ≥960 | ≥960 | ≥960 | ≥960 | ≥960 |
| Cabinet Size (W x H x D)mm | 480 x 480 x 85 | 480 x 480 x 85 | 480 x 480 x 85 | 480 x 480 x 85 | 732 x 732 x 85 |
| Cabinet Resolution (W x H) | 160 x 160 | 120 x 120 | 96 x 96 | 80 x 80 | 96 x 96 |
| Cabinet Weight (Kg/m ²) | 45 | 45 | 45 | 45 | 45 |
| Max Power Consumption (W/m ²) | ≤450 | ≤750 | ≤550 | ≤430 | ≤550 |
| Average Power consumption (W/m ²) | 202 | 338 | 250 | 195 | 248 |
| Viewing Angle | Degree: H | | | | 140° |
| | Degree: V | | | | 140° |
| Mini View Distance (m) | 3 | 4 | 5 | 6 | 7.5 |
| Use Temperature(°C) | Operating | -10°C~40°C/14°F~104°F | | | |
| | Storage | -20°C~50°C/-4°F~122 °F | | | |
| Input Voltage | 100~240V | | | | |
| Input Power Frequency (Hz) | 50Hz-60Hz | | | | |
| Failure Rate | <1/100,000 | | | | |
| Signal Input Format | SDI, RGBHV, YUV,YC, Composite, HDMI,DVI, SD/HD-SDI etc. | | | | |
| Life Time (hrs) | 100,000 | | | | |
| IP Level (Front / Rera) | IP 43 / IP30 | | | | |

Remark: Specifications are subject to change without notice.



BL.#7, Huamei Rd.#8, Songgang Av., Songgang Town, Bao'an District, Shenzhen, China.



Tel: 86-755-2359 0202



Fax: 86-755-2908 0303



E-mail: info@q-color.com



Web: www.q-color.com



International hotline:

86-755-2359 0202